





BL12206505

**FOG** 

# **TF095-FOG SENSOR-20W-IP66-WHITE-3000K-850°**

INDOOR > Indoor Bulkhead
OUTDOOR > Outdoor Wall Light
OUTDOOR > Outdoor Bulkhead

Indoor or outdoor use, IP66, with HF detector. Ideal for communities, garages and stairwells

# **Application domain**

- Parkings lots and underground passages
- Circulations areas
- Stairs
- Outdoor Circulations





2030 lm IRC >80

IP66

3000K









## **Electric data**

Total power (W)	20
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

# Photometric data

Color temperatures	3000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (Im)	2030lm (3000K)
ULOR	-





## **Technical data**

Diameter (mm)	300
Height (mm)	93.5
Recessed diameter (mm)	-
Weight (kg)	0.96
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK10
Incandescent wire test	850°C
IP Code	IP66
Use temperature range	-20 +50°
Body material	PC
Diffuser material	PC
Sensor	Haute fréquence
Driver included	Yes

#### Liefe time

L80 à 25° 50 000 h
--------------------

# **Supplementary data**

Warranty period	5 years
Light beam spread	110°
Tiltable	No
Connection type	Fast connect





#### **Accessories**

# | Distance : 6 m | Temporisation : 90 sec. | Sensibilité : 10 lux | Temporisation | Sensibilité : 10 lux | Sensibilité : 10 lu

#### **Atmosphere**



# Other



# Other





