





BL12146504

FOG

TF094-FOG SENSOR-14W-IP66-WHITE-3000K-850°

INDOOR > Indoor Bulkhead
OUTDOOR > Outdoor Wall Light
OUTDOOR > Outdoor Bulkhead

Indoor or outdoor use, IP66, with HF detector. Ideal for communities, garages and stairwells

Application domain

- Parkings lots and underground passages
- Circulations areas
- Stairs
- Outdoor Circulations



















Electric data

Total power (W)	14
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	3000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>5
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (Im)	1200lm (3000K)
ULOR	-





Technical data

Diameter (mm)	300
Height (mm)	93.5
Recessed diameter (mm)	-
Weight (kg)	0.96
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK10
Incandescent wire test	850°C
IP Code	IP66
Use temperature range	-20 +50°
Body material	PC
Diffuser material	PC
Sensor	Haute fréquence
Driver included	Yes

Liefe time

L80 à 25° 50 000 h

Supplementary data

Warranty period	5 years
Light beam spread	110°
Tiltable	No
Connection type	Fast connect





Accessories

| Distance : 6 m | Temporisation : 90 sec. | Sensibilité : 10 lux | Temporisation | Sensibilité : 10 lux | Sensibilité : 10 lu

Atmosphere



Other



Other





