



in partnership with

DRIVER RF-100W-4CH-24V

BL091002411

LED STRIP > LED Strip

DRIVERS AND ACCESSORIES > Alimentation et Accessoires

24V 100W power supply for RGB+W or single color. 4 channels 4.16A





Electric data

Total power (W)	100
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	push dim , yes with RF remote controller



FILE UPDATED ON 09/01/2023

Photometric data

Color temperatures	
Light source type	-
SDCM	
IRC	
Safety group (EN62778)	
Luminous flux (lm)	-
ULOR	

Technical data

Dimensions (mm)	244 x 64 x 32
Dimensions (mm)	244 X 04 X 32
Weight (kg)	0.46
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK04
Incandescent wire test	-
IP Code	IP20
Use temperature range	-20 +45°
Body material	PC
Diffuser material	-
Driver included	No

Liefe time



FILE UPDATED ON 09/01/2023

TOPLED NORDIC BE-LED. ALL RIGHTS RESERVED.


DRIVER RF-100W-4CH-24V - 2/3


Supplementary data

Warranty period	5 years
Light beam spread	
Tiltable	No
Connection type	Connector on the product


Other







Other





FILE UPDATED ON 09/01/2023