

< TOP LED </pre>

• be-led in partnership with

PROJECTOR **TF080-FLOODLIGHT 50W-IP65-4000K-120°** BL10506501

OUTDOOR > Outdoor Flood Light

High power led projector, tempered glass and aluminum body.

Application domain

- Outdoor residential
- Garden
- Outdoor Parking
- Outdoor lighting



Electric data

Total power (W)	50
Rated voltage (V)	230V
Distorsion harmonique	
Power factor	>0.9
Network frequencies	50Hz
Electric class	Ι
Dimmable	No



FILE UPDATED ON 04/04/2023



Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	6000lm (4000K)
ULOR	

Technical data

Dimensions (mm)	281 x 193 x 44
Weight (kg)	1.68
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	Black
IK Code	IK08
Incandescent wire test	850°C
IP Code	IP65
Use temperature range	-20 +50°
Body material	Aluminium
Diffuser material	Verre trempé
Driver included	Yes

Liefe time

L80 à 25°

50 000 h



FILE UPDATED ON 04/04/2023

TOPLED NORDIC BE-LED. ALL RIGHTS RESERVED.

Supplementary data

Warranty period	5 years
Light beam spread	120°
Tiltable	No
Connection type	Fil à connecter
Linked products	• TR08006501 - CONNECTOR IP65

Other





FILE UPDATED ON 04/04/2023