

RESIDENTIAL PROJECTOR

RESI FLOODLIGHT-30W-IP65-4000K-GRIS

BL10306551

OUTDOOR > Outdoor Wall Light

OUTDOOR > Outdoor Flood Light

Residential projector that meets the regulations on light pollution. Discreet and aesthetic, it fits well on the facade, above a garage door, in an alley...



Application domain

- Garages
- Outdoor residential
- Garden
- Outdoor lighting



30 W

2450
lm

IRC
>80

IP65

4000K

F



FILE UPDATED ON 21/11/2022

Electric data

Total power (W)	30
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	I
Dimmable	No

Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	2450lm (4000K)
ULOR	-



FILE UPDATED ON 21/11/2022



Technical data

Dimensions (mm)	25 x 141 x 117
Weight (kg)	0.54
Recessed depth under BA13 (mm)	-
Cable length	100 cm
Product color	Dark gray
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-25... +45°
Body material	Aluminium
Diffuser material	Verre trempé
Driver included	Yes

Liefe time

L70 à 25°	30 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	100°
Tiltable	No
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none">• TR08000003 - Tornado Stake 30W-50W• TR08006501 - CONNECTOR IP65



FILE UPDATED ON 21/11/2022





FILE UPDATED ON 21/11/2022