





RESIDENTIAL PROJECTOR

RESI FLOODLIGHT-20W-IP65-3000K-GRIS

BL10206550

OUTDOOR > Outdoor Wall Light **OUTDOOR** > Outdoor Flood Light

Residential projector that meets the regulations on light pollution. Discreet and aesthetic, it fits well on the facade, above a garage door, in an alley...



Application domain

- Garages
- Outdoor residential
- Garden
- Outdoor lighting



20 W

1600 lm IRC >80

IP65

3000K







Electric data

| Total power (W) | 20 |
|-----------------------|------|
| Rated voltage (V) | 230V |
| Distorsion harmonique | <30% |
| Power factor | >0.9 |
| Network frequencies | 50Hz |
| Electric class | I |
| Dimmable | No |

Power supply data

| Max. lamp per B10A circuit breaker | 20 |
|------------------------------------|----|
| Max. lamp per B16A circuit breaker | 25 |
| Max. lamp per C16A circuit breaker | 30 |

Photometric data

| Color temperatures | 3000K |
|----------------------------|----------------|
| Light source type | SMD |
| Including the light source | Yes |
| SDCM | SDCM>4 |
| IRC | >80 |
| Safety group (EN62778) | RG1 |
| Luminous flux (lm) | 1600lm (3000K) |
| ULOR | - |





Technical data

| Dimensions (mm) | 22 x 112 x 95 |
|--------------------------------|---------------|
| Weight (kg) | 0.36 |
| Recessed depth under BA13 (mm) | - |
| Cable length | 100 cm |
| Product color | Dark gray |
| IK Code | IK06 |
| Incandescent wire test | 650°C |
| IP Code | IP65 |
| Use temperature range | -25 +45° |
| Body material | Aluminium |
| Diffuser material | Verre trempé |
| Driver included | Yes |

Liefe time

| L70 à 25° 30 000 h |
|---------------------------|
|---------------------------|

Supplementary data

| Warranty period | 3 years |
|-------------------|---|
| Light beam spread | 100° |
| Tiltable | No |
| Connection type | Fil à connecter |
| Linked products | TR08000002 - STAKE Tornado 10W-20W TR08006501 - CONNECTOR IP65 |









