





HIBAY

HIBAY ECOPLUS 200W-4000K-IP65-120°

BL112006523

INDOOR > Highbay

Economical led fixture of 160 lm/W



Application domain

• Industrial facilities





32400 lm IRC >82 IP65

4000K



Electric data

| Total power (W) | 200 |
|-----------------------|------|
| Rated voltage (V) | 230V |
| Distorsion harmonique | - |
| Power factor | >0.9 |
| Network frequencies | 50Hz |
| Electric class | I |
| Dimmable | No |

*be-lec

FILE UPDATED ON 21/04/2023

Photometric data

| Color temperatures | 4000K |
|----------------------------|-----------------|
| Light source type | SMD |
| Including the light source | Yes |
| SDCM | SDCM>5 |
| IRC | >82 |
| Safety group (EN62778) | RG1 |
| Luminous flux (Im) | 32400lm (4000K) |
| ULOR | - |

Technical data

| Diameter (mm) | 320 |
|--------------------------------|--------------|
| Height (mm) | 155 |
| Recessed diameter (mm) | - |
| Weight (kg) | 2.24 |
| Recessed depth under BA13 (mm) | - |
| Cable length | 30 cm |
| Product color | Black |
| IK Code | IK08 |
| Incandescent wire test | 850°C |
| IP Code | IP65 |
| Use temperature range | -25° +55° |
| Body material | Aluminium |
| Diffuser material | - |
| Driver included | Yes |
| Recoverable | Non concerné |



Liefe time

| L70 à 25° | 50 000 h |
|-----------|----------|

Supplementary data

| Warranty period | 5 years |
|-------------------|--|
| Light beam spread | 120° |
| Tiltable | No |
| Connection type | Fil à connecter |
| Linked products | BL08000011 - TF057 High bay suspension chain |

Other



