

LED PANEL

PANEL TECH-600X600-3CCT

BL04302007

INDOOR > Office Recessed Fixture

120lm/W micro prismatic led panel. 3 temperature colors to select on the product. 3600 lm in 3000K, 3900 lm in 4000K and 3600 lm in 6000K.



Application domain

- Meeting room
- School
- Office



Electric data

Total power (W)	30
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz
Electric class	III
Dimmable	No

Photometric data

Color temperatures	3000K / 4000K / 6000K
UGR	<19
Light source type	-
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	3900lm (4000K)
ULOR	-

Technical data

Dimensions (mm)	595 x 595 x 30
Weight (kg)	2.04
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK04
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-25... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	90°
Tiltable	No
Connection type	Bornier avec repiquage
Linked products	<ul style="list-style-type: none">• BL08000013 - TF066-Protrusion frame 600x600• BL08000002 - TF018 Mechanically welded projection frame• PL09302003 - DALI PUSH DIM POWER SUPPLY

Other

